

**Amendments to the Specification**

Please replace paragraph [0003] with the following amended paragraph:

[0003] One solution to these problems is to provide cooling holes 44a, 44b in Figure 4, to admit cooling air through the motor 22. The invention provides additional strategies to cool motor 22.

Please replace paragraph [0008] with the following amended paragraph:

[0008] In yet another aspect this invention comprises ~~An~~ an electric fan for use on a vehicle comprising: an electric motor having an airflow passageway, and a fan assembly mounted on a shaft of the electric motor, the fan assembly comprising: a hub on which a plurality of fan blades are situated for creating an axial air flow, and the hub further comprising a plurality of ~~vanes~~ ribs at least partially surrounding a cover of the electric motor for creating a radial air flow used for cooling the motor and then directed toward the axial air flow.

Please replace paragraph [0014] with the following amended paragraph:

[0014] Fig. 1 illustrates a fan assembly or fan 10 in accordance with one embodiment of the invention. The fan 10 comprises a plurality of fan blades 12 that extend radially between a hub 14 and a ring shroud 15. The hub 14 comprises a circumferential

ring- 18 to which the fan blades 12 are integrally formed and a front wall 17 (Fig. 2). A plurality of radial ~~vanes or~~ ribs 20 rise from the front wall 17 and extend between the connector 16 and circumferential ring 18, as illustrated in Fig. 2. It should be understood that the fan 10 may be a one-piece construction molded from plastic or other suitable material.

Please replace paragraph [0015] with the following amended paragraph:

[0015] Fig. ~~3~~2 illustrates an exploded fragmentary view illustrating an electric motor 22 for rotatably driving fan 10. The electric motor 22 comprises a shaft 24 which is received in the aperture 26 defined by connector- 16 and secured thereto by conventional means, such as a nut or spring clip attachment design. Air holes 44a and ~~44d~~44b (Fig. 4) permit air to flow through the motor 22 as is conventionally known.

Please replace paragraph [0017] with the following amended paragraph:

[0017] Note that the motor 22 comprises a housing or casing 25 having a circumferential flange or bulkhead 30 (Figs. 2 and 3) that extends radially outward from the casing 25 of motor 22. Note that the flange 30 comprises a surface 30a that is situated in proximate relation to edge- 27 of ~~vane~~rib 20, as illustrated in Fig. 3. Thus, as best illustrated in Fig. 3, notice that the edges- 27, 23a and 23b of each rib ~~or vane~~ 20 and the

surface 17a cooperate with the surfaces 22a, 25 and 30a, respectively, to define a low pressure channel or area 27a through which air may flow. Ideally, it is desired to have a distance or gap 28a be small or minimized to facilitate creating a low-pressure chamber between the hub 14 and the motor 22 and flange 30. It is desirable to have the axial gap 28a between surface 23b and 30a to be optimized and dimensioned along with the respective diameter of the inside of the hub wall 18 and outside diameter of the flange. There is also an optimum relationship between the constraints defining the region 28a as shown in Figure 3 that maximizes the low pressure level of the said low pressure channel or area. The defining constraints of the region 28a are the rear edge of the rib 20 defined as 23b, the forward surface of the flange 30, indicated by 30a, the inner diameter of the hub wall 18, defined by 18a and expressed as double arrow E, and the outer edge of the flange 30, defined by 30b and also expressed as the double arrow F. The relationship between the axial gap and the respective diameters of the inner hub wall and the outer diameter of the flange must be jointly optimized to maximize the cooling flow drawn through the motor.

Please replace paragraph [0018] with the following amended paragraph:

[0018] As best illustrated in Figs. 1 and 2, the generally L-shaped ~~vanes~~ ribs 20 and wall 18 make up or define an area 36 for receiving the electric motor 22 such that the ~~vanes~~ ribs, or at least portions 23 (Fig. 3) of ~~vanes~~ ribs 20 surround the housing 25 (Fig. 3).

In the embodiment being described, the clearance between the surfaces-~~22~~ 27, 23a and 23b and the surface 22a, 25 and 30a should be minimized as much as possible. It has been found that a channel- 27a having a relatively small clearance-~~28~~ 28b will increase a rotational speed (i.e., in the direction of arrow B in Fig. 3) of air confined within the area or chamber 36, which further reduces the pressure in area 27a relative to the area outside of area 36.

Please replace paragraph [0019] with the following amended paragraph:

[0019] Thus, it should be appreciated that the invention provides a cooling system for use in a vehicle. Note that the plurality of fan blades 12 direct air flow in- the direction of arrow A in Fig. 3 which indicates a mixed axial and radial exit airflow character. The plurality of ribs 20 direct air flow in a radial direction indicated in arrow B in Fig. 3. Note that the channel- 27a directs the air flow generally radially across the face 22a of motor 22, then axially along the housing 25 of motor 22 and then again radially along surface 30a toward the air flow A. Thus, one feature of the invention is that-~~that the ribs or vanes-22~~ 20 ultimately direct air flow toward the plurality of blades 12 which direct air flow in a mixed axial and radial character per direction arrow A.- The motor cooling exit flow is assisted or entrained by the presence of the higher velocity airflow generated by the plurality of blades 12. This entrainment by the higher velocity main cooling fan airflow that occurs in the

general area 40 that increases cooling airflow through the motor, which further improves cooling of the electric motor 22.

Please replace paragraph [0020] with the following amended paragraph:

[0020] Advantageously, this invention provides an electric motor having an air flow passageway and further comprising a fan assembly having a hub that cooperates with the ~~cover of the motor~~ motor housing to form a low pressure area referred to above and that communicates with the air flow passageway to facilitate improving air flow through the electric motor.

Please replace paragraph [0021] with the following amended paragraph:

[0021] Another advantage of the invention is that it provides an electric fan for use on a vehicle which is designed to generate cooling airflow through the motor 22 that moves radially- across the front face 22a of motor 22 and toward the area 40 (Fig. 3) where the air flowing through channel- 27a which- is directed toward area 40 where it meets and is entrained by the- air flow generated by fan blades 12 and indicated by arrow A in Fig. 3.

Please replace paragraph [0022] with the following amended paragraph:

[0022] Notice also that the invention provides an electric fan having a hub 14 that extends or partially surrounds the housing 25, as illustrated in Fig. 3. Notice also that the fan blades or a portion of the fan blades 12 may also extend over the motor 22 in generally opposed relationship to the motor housing 25 as shown. Thus, the ribs 20 are formed to surround at least a portion of the motor housing surface 25 to further facilitate creating the low pressure area and the channel 27a for providing a controlled air flow across surfaces 22a, 25 and 30a.

Please replace paragraph [0023] with the following amended paragraph:

[0023] The motor 22 comprises the holes or openings 44a and 44b that permit air to flow through motor 22. Notice that the invention facilitates causing air to flow in the direction of dashed arrow D in Figs. 3 and 4. In operation, the hub 14 rotates as indicated by arrow C in Fig. 4. Each portion 21 and portion 23 sweeps air across the surfaces 22a and ~~33a~~ 25 (Fig. 3). Centrifugal force pushes the swept air radially through channel 27a and generally radially outward in the direction of dashed arrow D in Fig. 3. As the air exits channel 27a, it is further urged toward the fan blades 12 which forces the air in the direction of arrow A. Further,- the pressure at area 40 (Fig. 4) is greater than the pressure in channel 27a. The flange 30 helps reduce flow recirculation across area 44 and maintains the low pressure in the channel 27a between the hub 14 and motor 22.

Please replace paragraph [0024] with the following amended paragraph:

[0024] The low pressure in area or channel 27a air to pass through holes 44a, 44b (Fig. 4) in the motor-casing housing 25. While within the motor 22, the air passes along the rotor (not shown), cooling the rotor, the associated stator (not shown) and other internal components of the motor 22. This air is then expelled from the displacement and injected toward the area 40 in the direction of dashed arrow D (Fig. 3).

Please replace paragraph [0025] with the following amended paragraph:

[0025] The shape and number of ribs 20 within the hub 14 and the clearance between the ribs ~~28~~ 20 and ~~casing 23~~ motor housing 25 and flange 30 must be selected to ensure air in the area 28b closely follows the rotation of the hub 14. The number of vanes 20 must also not be so high as to severely block motor cooling air-flow passage. Increased rotational speed of the fan 10 will increase the air flow in the direction of arrow- D (Fig. 4) and should resultingly increase cooling flow through motor 22. An increase in an overall diameter of the hub 14 will also work to lower the pressure in the area 36- and therefore, increase motor cooling flow.

Please replace paragraph [0026] with the following amended paragraph:

[0026] Advantageously, this system and method provides a hub having a plurality of ~~vanes or~~ ribs 20 that cooperate with a motor casing ~~23~~ housing 25 to define the coupling channel 36. The coupling channel 36 defines a low-pressure area around the motor casing ~~23~~ housing 25 which facilitates urging air through the motor casing ~~23~~ 25 which, in turn, facilitates cooling of the motor 22.

Please replace paragraph [0027] with the following amended paragraph:

[0027] While the system and method described, constitute preferred embodiments of this invention, it is to be understood that the invention is not limited to this precise system and method, and that changes may be made in either without departing from the scope of the inventions, which is defined in the appended claims.